

BV Series

Specifications

BV5160 SC-14 - BV5160 NET



Kubota Models	BV5160 SC14	BV5160NET
Weight and Dimensions		
Length (in)	176"	
Width (in)	99"	
Height (in)	106"	
Weight (lbs)	7165	6965
Bale chamber		
Diameter Min (in)	24"	
Diameter Max (in)	65"	
Bale Width(in)	47"	47"
Bale Height(in)	60"	60"
Bale Formation	5 Belts + 3 Rollers	5 Belts + 3 Rollers
Endless Belts	•	•
Bale Ramp	•	•
Pick-up		
Working Width (in)	86"	
Number of Tine Rows	5	5
Tine Spacing (in)	2.36"	
Windguard	Roller Wind Guard	
Pneumatic Gauge Wheel	•	
Flare to Flare Pickup		86"
Lift		Hydraulic
Pickup Protection		Radial Clutch
Intake System		
Fork Feeder	-	
Protection, cam clutch	-	
SuperCut-14 Knives	•	
Single Knife Protection	•	
Unblocking System	Drop Floor	
Driveline		
Chain	1.25"	1.25"
1 1/4" Main drive chain	•	
Wide angle PTO Shaft	•	
Shear Bolt Protection	-	
Cam Clutch Protection	•	
Binding		
Binding	Net/Twine	Net
Monitor	Focus	Focus
Twine	double arm	NA
Operations		
ISOBUS	•	
Focus Terminal	•	
IsoMatch Tellus	o	
Hydraulic Outlets	1SA + 1DA	
Wheels and Axles		
11.5/80-15	-	
15.0/55-17	•	
19.0/45-17	o	
500/45-22.5	o	
Others		
PTO (rpm)		540CV
PTO Protection		CamClutch
Minimum Horsepower (hp)		75
Tires		31x13.5x15
• = standard o = optional - = not available		

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional and not standard equipment. Please consult your local Kubota dealer for warranty, safety or product information. For your safety, Kubota strongly recommend the use of a seat belt in all applications.