

Specifications

| Model | | M6H-101 | |
|--|-----------------|---|--|
| | | SHD | |
| | | 4WD | |
| Engine | | | |
| Type (make: Kubota) | | V3800-TIEF4-Direct Injection, Water-cooled 4 Cycle Diesel, Common Rail System, Turbocharger, Intercooler, DPF, DOC, SCR | |
| Cylinders and displacement | cu. in. (cc) | 4-cylinder, 230 (3769) | |
| Engine gross power (97/68EC) | HP (kW) | 104.4 (77.9) | |
| PTO power (at rated RPM) | HP (kW) | 84.0 (62.6) | |
| Alternator | Amp | 80 | |
| Rated engine speed | rpm | 2600 | |
| Fuel tank capacity | gal. (ℓ) | 46 (175) | |
| Transmission | | | |
| No. of speeds | Standard | F24 / R24 (with creep) | |
| Traveling speed | mi/h (km/h) | 0.11 – 16.37 (0.18 – 26.34) | |
| Shuttle | | Electro-hydraulic | |
| Clutch | | Hydraulic Wet Clutch | |
| Rear wheel brake | | Hydraulic Wet Disk Type | |
| Mechanical differential lock | | Front / Rear | |
| PTO | | | |
| Clutch | | Hydraulic Wet Clutch | |
| Revolution | rpm | 540 (540/1000 factory optional) | |
| Hydraulics | | | |
| Type | | Open-Center | |
| Draft control | | Top Link Draft Sensing | |
| Lift capacity at 24 in. behind lift point (OECD) | lbs. (kg) | 3858 (1750), 5732 (2600) with 2 assist cylinders (option) | |
| Lower link | | Telescopic | |
| Category | | II | |
| Rear remotes | | 2 standard (3rd & flow control valve optional) | |
| Pump output (remote) | gal/min (ℓ/min) | 17.6 (66.6) | |
| Exterior | | | |
| Hood | | Full-open | |
| Dimensions | | | |
| Wheel base | in. (mm) | 95.3 (2420) | |
| Minimum ground clearance* | in. (mm) | 25.8 (655) | |
| Tread* | Front | 61.6, 65.6, 72.0, 75.8, 79.7 (1565, 1665, 1830, 1925, 2025) | |
| | rear | 60.8, 64.8, 73.4, 77.2, 81.1 (1545, 1645, 1865, 1960, 2060) | |
| Overall length | in. (mm) | 168.3 (4275) | |
| Overall height (ROPS unfolded) | in. (mm) | 111.6 (2835) | |
| Overall width | in. (mm) | 79.9 (2030) | |
| Weight | lbs. (kg) | 8157 (3700) | |
| Turning radius w/o brake | ft. (m) | 21.0 (6.4) | |
| Standard tires | Front | 13.6-38 | |
| | rear | 13.6-38 (steel) | |

* When standard tires are equipped

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



Kubota
Genuine Parts
for maximum
performance,
durability and
safety

©2017 Kubota Corporation

Kubota

KUBOTA TRACTOR CORPORATION

1000 Kubota Drive, Grapevine, TX 76051 Tel 888-4 KUBOTA

Visit our web site at: kubotaUSA.com

